



INTERNATIONAL PROTECTION IP65

△ DESIGNATES CRITICAL CHARACTERISTICS

NOTES:

- △ 1-.040-.150 MOTION TO CLOSE CONTACTS.
- 2-PLASTIC PARTS - DELTON™, UV STABLE, FUEL RESISTANT THERMOPLASTIC.
TERMINALS - NICKEL PLATED BRASS.
CONTACT - BERYLLIUM COPPER.
BOOT - THERMOPLASTIC ELASTOMER.
- 3-DATE CODE INDICATING YEAR, MONTH, AND DAY OF MONTH
MANUFACTURED STAMPED ON HOUSING.
- △ 4-INTEGRITY OF WELD & SWITCH FUNCTIONALITY TESTED AFTER ASSEMBLY.
- 5-DELTA IS RESPONSIBLE FOR COMPLIANCE TO THIS SPECIFICATION.
THE FUNCTION AND ADEQUACY OF THE SAFETY "SYSTEM" IN WHICH THIS COMPONENT IS USED IS THE RESPONSIBILITY OF THOSE THAT DESIGN AND BUILD THE SYSTEM (INCLUDING BUT NOT LIMITED TO THE SEAT DESIGN, SWITCH LOCATION, FOAM DENSITY AND DESIGN).
- 6-THIS PRODUCT IS COVERED BY ONE OR MORE OF THE FOLLOWING U.S. PATENTS:
4,812,604; 4,795,865. OTHER PATENTS APPLIED FOR.

NORMALLY OPEN SWITCH

